

## Graduated and volumetric plasticware

### Graduated beakers, low form

#### Material:

Polypropylene

#### Description:

Conforms to ISO 7056 - 1981 (E) and BS 5404 Part 1. New polypropylene giving very high translucency. Autoclavable to 121 °C for 20 min. continuous work at 100°C. Permanent graduations are moulded in for reproducibility. Excellent chemical resistance.



Code	Capacity ml	Subdivis.ml	Tolerance ml	O.D. Ø mm	h mm	Wall thickness
<b>1801</b>	<b>25</b>	<b>1</b>	<b>+/- 10%</b>	<b>34</b>	<b>49</b>	<b>1,3</b>
<b>1802</b>	<b>50</b>	<b>2</b>	<b>+/- 10%</b>	<b>41</b>	<b>60</b>	<b>1,3</b>
<b>1803</b>	<b>100</b>	<b>5</b>	<b>+/- 10%</b>	<b>51</b>	<b>72</b>	<b>1,5</b>
<b>1805</b>	<b>250</b>	<b>10</b>	<b>+/- 10%</b>	<b>71</b>	<b>95</b>	<b>1,7</b>
<b>1806</b>	<b>500</b>	<b>10</b>	<b>+/- 10%</b>	<b>87</b>	<b>119</b>	<b>1,8</b>
<b>1808</b>	<b>1000</b>	<b>20</b>	<b>+/- 10%</b>	<b>109</b>	<b>147</b>	<b>1,8</b>
<b>1809</b>	<b>2000</b>	<b>50</b>	<b>+/- 10%</b>	<b>132</b>	<b>183,5</b>	<b>1,8</b>
<b>811</b>	<b>3000</b>	<b>500</b>	<b>+/- 10%</b>	<b>158</b>	<b>201</b>	<b>2,5</b>
<b>812</b>	<b>5000</b>	<b>500</b>	<b>+/- 10%</b>	<b>188,5</b>	<b>229</b>	<b>2,5</b>

# BEAKER PLASTIC, PP (LP/ITALY)



VOLUME (ML)	GRADUTION (ML)	DIA. (MM)	HEIGHT (MM)
50 ML	10	45	60
100 ML	20	55	70
250 ML	50	75	90
600 ML	100	100	125
1000 ML	100	125	150