

Laboratory – Water Purification system

# Automatic Water Still

www.promat.hk

TEL - 2661 2392



- Fully Automatic Operation System
- Sensing water level in boiling chamber to protect heater from over heating
- Check water supply to control distillation
- Check water level in reservoir to start and stop distillation automatically

| Specification   |       |   |
|-----------------|-------|---|
| Model           |       | LWD-3004  |
| Capacity        |       | 4.0 l /hour   |
| Dimensions (mm) |       | 740 (W) x 345 (D) x 513 (H)   |
| Heater          |       | 3.0 kW  |
| Cooling Water   |       | Approx. 30~50 l   |
| Material        | Inner | Stainless Steel Boiler<br>Stainless Steel Storage Tank                  |
|                 | Outer | Powder Coating Steel Case   |
| Reservoir       |       | 11l SUS Storage Tank  |
| Safety Device   |       | Over Temp Protector<br>Water Float Level Sensor<br>Water Supply Cut Off |
| Operation       |       | Full Automatic Operation  |
| Signal lamp     |       | Distill, Full, Water  |
| Electric supply |       | 220V, 50Hz  |

**PROMAT (HK) Limited**

TEL: 2661 2392 FAX: 2661 2086 Email: info@promat.hk  
Address: 901 New Trend Center, 704 Prince Edward Road East, Sanpokong, Kowloon, Hong Kong